



INSTALLATION INSTRUCTIONS
THE FOLLOWING INSTRUCTIONS MUST BE PREPARED DURING THE TIME OF CONSTRUCTION

 FREE ZONE ON WALL BEHIND THE CLIMBING SYSTEM WITHIN THE MARKED ZONE. THERE MUST BE NO OBSTRUCTIONS THAT COULD AFFECT THE MOUNTING OF THE WALL BARS, FOR EXAMPLE WIRING, VENTILATION DUCTS OR RADIATOR PIPES.

THE WALL MUST BE VERTICAL WITHOUT ANY OBSTRUCTIONS.

 **FOR TIMBER WALLS:**
 MARKINGS SHOW WHERE TIMBER REINFORCEMENTS WITH A THICKNESS OF 90MM AND A WIDTH OF 145MM ARE NEEDED. ALL REINFORCEMENTS MUST BE LOCATED DIRECTLY BEHIND THE WALL SURFACE TO GIVE A RIGID FASTENING WHEN MOUNTING THE WALL BARS ONTO THE WALL SURFACE. ALL REINFORCEMENTS MUST BE WALL ANCHORED TO THE WALL. THE LOAD PER RUNNING METER ON THE INSTALLATION BEAM IS APPROXIMATELY 200 KILOGS. ALL WALLS ARE VIEWED FROM THE INSIDE OF THE ROOM. PLASTERBOARD MUST NOT BE THE OUTER LAYER.

ATTACHMENTS FOR THE WALL ARE NOT INCLUDED.



Rev.	Description:	Date:	By:

Drawing Name: **GYM-WBS-3 Triple Section Wall Bar**

Drawn By:	MS
Date:	24-05-12
Checked By:	GIK
Scale:	1:30 @ A3

Please note:
 This drawing is intended as a guide only. Sport Alpha UK should be consulted to approve any fixing provisions prior to installation. Please note that non-standard fixings which require specialised fixing or additional drilling, etc. may incur additional charges. If in doubt, contact us.

Sport Alpha UK Ltd
 Unit 3, Burnbank Business Units
 Strathclyde Park
 Allens Industrial Estate
 Aberdeen AB12 3LF

T: 01224 899059
E: info@sportalphauk.com
W: www.sportalphauk.com